

TECHNICAL DATASHEET

VRILUX

Ref. MO60332

Safety Glasses







The +

Flexible and adjustable temple Temple angle adjustment Upper and side protection

PURCHASE PACKAGING

 Ref.
 Size
 Inner
 Carton

 60332
 10
 120

SALES PACKAGING



Individual pack

See also

DESCRIPTION

Vrilux safety glasses. Clear polycarbonate lens, UV treatment, anti-fog treatment N, side and frontal protection, temples angle and 5 positions length adjustment

SECTORS

Heavy & process industries

Mechanicals constructions

Light Industries

Maintenance

Infrastructure, building industry

Construction - finishing work

DIY

VARIANTS



MO60336

TECHNICAL FEATURES

Shape Safety Glasses

Weight 39g

Lens Polycarbonate 2.4mm

Lens marking 2-1.2 1FN

Frame Polycarbonate

Frame marking F Temple material Nylon **Temples** Adjustable in height and length

Shade Clear

Main risk Eye protection

Color Black

Features Anti-fog coating N standard

Anti-UV coating

Other features Monobloc lens

5 position temple length adjustment

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate PPE22162354

Delivered by INSPEC International B.V. (2849) Beechavenue 54-1119 PW Schiphol-Rijk Netherlands

((

EPI CAT. II

EN166:2001 Specifications (optical quality, resistance to usual risks, mechanical risks, resistance

to impacts)

EN170:2003 Ultraviolet filters

RETAILER STAMP

MAJ 24/03/2023