coverguard

TECHNICAL DATASHEET

STYLUX

Ref. MO60510

Safety Glasses





The +

Panoramic vision Adjustable temple Anti-slip nose bridge Side protection

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
60510	-	10	120

SALES PACKAGING



Hangable individual polybag

See also



DESCRIPTION

Curved and smoke polycarbonate lens, frame and temple made of nylon, temples angle and length adjustment, anti-slip nose piece, Wraparound with side protection

SECTORS

Light Industries

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

coverguard

STYLUX

TECHNICAL FEATURES

Shape	Safety Glasses
Weight	29g
Lens	Polycarbonate 2.3mm
Lens marking	2-1.2 1FTK
Frame	Nylon + polycarbonate
Frame marking	FT
Temple material	Nylon

TemplesAdjustable in height and lengthShadeClearMain riskEye ProtectionColorBlackFeaturesAnti-scratch coating K standard
Anti-UV coatingOther featuresSPORT STYLE

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 776

Delivered by INSPEC International Ltd. (0194) 56 Leslie Hough Way- Salford- Greater Manchester M6 6AJ United Kingdom

CE	EPI CAT. II
EN166:2001	Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)
EN170:2003	Ultraviolet filters

RETAILER STAMP

MAJ 24/03/2023