coverguard	ECHNICAL DATASHEET	
	Ref. MO60516	
Safety Glasses		
	K UV T The	+
	Panoramic vision Adjustable temple Anti-slip nose bridge Side protection	
	PURCHASE PACKAGING	
	Ref. Size Inner Carton	n
	60516 - 10 120	
	SALES PACKAGING	
	×1	
	Hangable individual polybag	
DESCRIPTION	See also	
Curved and yellow polycarbonate lens, frame and temple made of n	lon,	
temples angle and length adjustment, anti-slip nose piece, wrapard with side protection		
SECTORS	MO60513	3
Light Industries		
Infrastructure, building industry	MO60610	
Construction - finishing work		
Transport (excluding manufacturing) and logistics		
Services and distribution		

ด

## coverguard

## STYLUX

## **TECHNICAL FEATURES**

Shape	Safety Glasses
Weight	29g
Lens	Polycarbonate 2.3mm
Lens marking	2-1.2 1FTK
Frame	Nylon + polycarbonate
Frame marking	FT
Temple material	Nylon + polycarbonate

Temples	Adjustable in height and length
Shade	Yellow
Main risk	Eye protection
Color	Black
Color 2	Black
Features	Anti-scratch coating K standard
	Anti-UV coating
Other features	SPORT STYLE

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate 776

Delivered by INSPEC International Ltd. (0194) 56 Leslie Hough Way- Salford- Greater Manchester M6 6AJ United Kingdom

CE	EPI CAT. II
EN166:2001	Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)
EN170:2003	Ultraviolet filters

RETAILER STAMP

MAJ 24/03/2023