

Ref. 6PHW200

### Vented Helmet General Use



### The +

#### PERFORMANCE

- High resistance level (lateral deformation(LD), low temperature - 30°C)
- ABS Shell

#### COMFORT

- Side ventings
- Integrated safety glasses
- Good fitting and lightweight feeling (head balance)
- Easy adjustment by ratchet
- Wide field of vision thanks to the short peak
- 3D textile sweatband

#### LIGHTWEIGHT

- 450g

Compatible with badge holder (6POBA) and earcups (6MX3000NSI)

#### DESCRIPTION

PHOENIX WIND Safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, side ventings, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 points chinstrap as a standard

#### SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Regional/public authorities
- Infrastructure, building industry

#### APPLICATIONS

Construction site, building and public works, industry...

#### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHW200NSI	-		16

#### SALES PACKAGING



Individual polybag

See also

## TECHNICAL FEATURES

Shape	Safety helmet	Color	Blue
Weight	450g	Color 2	Black
Shade	Clear	Features	ABS Shell
Harness features	6 points harness made of polyethelene		LDPE 6 points harness
Main risk	6 textile webbings	Service life	Size adjustment from 52 to 63 cm
Shell material	Prevention from falling objects and head injuries or head trauma		Manufacturing date indicated under the peak
	ABS	Adjustment	Shelf life: Storage for 2 years in standard conditions
			Use for 5 years in good conditions
			Adjustment by ratchet from 52 to 63 cm

## STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2314

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy



EPI CAT. II

EN166:2001

Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)

EN397:2012 + A1:2012

Industrial safety helmets

COVERPERF - Skincare

Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.



RETAILER STAMP

MAJ 26/05/2023