

Ref. **9GARH70**

Multipurpose

High

High shoes



**HRO**



The +

- \* Padded collar and bellows tongue for snug fit.
- \* Heel scuff cap.
- \* Shock absorbing EVA midsole.

### PURCHASE PACKAGING

| Ref.       | Size | Carton |
|------------|------|--------|
| 9GARH70037 | 37   | 6      |
| 9GARH70038 | 38   | 6      |
| 9GARH70039 | 39   | 6      |
| 9GARH70040 | 40   | 6      |
| 9GARH70041 | 41   | 6      |
| 9GARH70042 | 42   | 6      |
| 9GARH70043 | 43   | 6      |
| 9GARH70044 | 44   | 6      |
| 9GARH70045 | 45   | 6      |
| 9GARH70046 | 46   | 6      |
| 9GARH70047 | 47   | 6      |

*Some sizes may only be available in certain countries*

### DESCRIPTION

GARNET is a leather safety shoe. The back of the model is equipped with a reinforcement to increase the protection and durability of the shoe. This model has a composite toe cap and a textile anti-perforation sole to make it a completely non-magnetic model. It is also equipped with a sole that is resistant up to 300°C on contact (for 1 minute).  
Note: GARNET 9GARH70 replaces the ALTAITE 9ALTH model.

### SECTORS

Mining

Extracting Oil and Gas

Energy (production and distribution)

Infrastructure, building industry

## TECHNICAL FEATURES

|                         |  |               |                             |
|-------------------------|--|---------------|-----------------------------|
| Color                   | Brown                                      | Insole        | Removable, textile and foam |
| Color 2                 | Red  | Main assembly | Cemented                    |
| Upper                   | Rectified leather and polyurethane coating | Closing       | Lacing closure              |
| Toecap                  | Composite                                  | Lining        | Breathable 3D mesh          |
| Puncture resistant sole | Textile                                    |               |                             |
| Midsole                 | EVA  |               |                             |
| Outsole                 | Rubber nitrile                             |               |                             |

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/02/22/0213

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

SRC

HRO

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Heat contact resistant outsole (60 seconds at 300°C)

RETAILER STAMP

MAJ 30/06/2022