

Ref. **9TEKL50**

Indoor and dry environments

Low

High shoes



**HRO**



The +

- \* Breathable upper and lining.
- \* Padded collar and bellows tongue: snug fit.
- \* Reflective strip: visibility.

### PURCHASE PACKAGING

Ref.	Size	Carton
9TEKL50039	39	6
9TEKL50040	40	6
9TEKL50041	41	6
9TEKL50042	42	6
9TEKL50043	43	6
9TEKL50044	44	6
9TEKL50045	45	6
9TEKL50046	46	6

### DESCRIPTION

Composite toecap  
 Antipenetration textile Wellmax sole  
 External sole in Rubber  
 Textile tightening loops, High shoes plastic hooks  
 Padded collar  
 Upper in PU Nubuck and mesh  
 Breathable mesh lining  
 Padded tongue

### SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

### APPLICATIONS

Painter,  
 Electrician,  
 Storekeeper, ...

**TECHNICAL FEATURES**

<b>Color</b>	Black	<b>Lining</b>	Breathable 3D mesh
<b>Color 2</b>	Grey		
<b>Upper</b>	Polyamide mesh / Polyurethane		
<b>Toecap</b>	Composite		
<b>Puncture resistant sole</b>	Textile		
<b>Outsole</b>	Rubber nitrile		
<b>Insole</b>	Removable, textile and foam		
<b>Main assembly</b>	Cemented		
<b>Closing</b>	Lacing closure		

**INSTRUCTION FOR USE AND STORAGE**

**Instructions for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the shoes, when not in use, in a dry, clean and airy place. The tim influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

**STANDARD(S)**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

**EN ISO 20345:2011**

**S1P**

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

**SRA**

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

**HRO**

Heat contact resistant outsole (60 seconds at 300°C)

RETAILER STAMP

MAJ 25/03/2022